



## NF-S12B redux-1200 PWM

### Product specifications

Date

03.07.2015

Rascom Computer Ges.m.b.H.  
Linzer Strasse 237  
A-1140 Vienna, Austria

Tel. +43 (1) 494 13 95 -0  
Fax. +43 (1) 494 13 95 -10  
[sales@noctua.at](mailto:sales@noctua.at)


# 1. General specifications

## 1.1. Mechanical specifications

|                           |                   |
|---------------------------|-------------------|
| Dimensions (without AVP*) | 120x120x25 mm     |
| Dimensions (with AVP*)    | 120x120x27 mm     |
| Wire length               | 400 mm            |
| Weight                    | 140g              |
| Rotational direction      | Counter-Clockwise |

\* AVP: Anti-vibration pads

## 1.2. Dimensions



## 1.3. Parts & materials

|                         |                         |
|-------------------------|-------------------------|
| Plastic type - frame    | PBT GF30                |
| Plastic type - impeller | PBT GF30                |
| Bearing                 | SSO                     |
| Wire                    | 26 AWG w/ Mesh-Sleeving |
| Connector type          | A2543-4PIN (or equal)   |


## 1.4. Standards

|                        |                                                                       |
|------------------------|-----------------------------------------------------------------------|
| Production standards   | Produced according to ISO9001 & ISO14001                              |
| Safety standards       | EN55032, EN55035, EN62368-1                                           |
| Enviromental standards | RoHS according to EU directive 2011/65/EU-RoHS and amendment 2015/863 |
| UL listed (E356416)    | Yes                                                                   |

## 1.5. Flammability

|                             |                       |
|-----------------------------|-----------------------|
| Plastic housing and frame   | UL 94 V-0             |
| Printed Circuit Board (PCB) | UL 796, UL 94 V-0     |
| Cable                       | UL 1007               |
| Mesh sleeving               | UL 1441 VW-1, E203950 |
| Heat shrink tubing          | UL 224 VW-1, E203950  |
| Connector                   | UL 94 V-0             |

## 1.6. Labels



### Main label

- Model number
- Rated voltage
- Rated power consumption
- Rated current
- Enviromental & safety standards

### Side label (printed in white)

- Production date
- Internal reference numbers



## 1.7. Environmental specifications

|                       |                  |
|-----------------------|------------------|
| Operating temperature | -10 °C to +70 °C |
| Operating humidity    | 15% to 90%       |
| Storage temperature   | -20 °C to +75 °C |
| Storage humidity      | 15% to 90%       |
| Protection level      | IP50             |

## 2. Electrical specifications

### 2.1. Wire specifications

|       |                       |
|-------|-----------------------|
| Pin 1 | Black: Ground (GND)   |
| Pin 2 | Yellow: Voltage (Vcc) |
| Pin 3 | Green: RPM Signal     |
| Pin 4 | Blue: PWM Signal      |

### 2.2. Motor specifications


|                                  |                                                                                                                              |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Number of poles / slots / phases | 4/4/1                                                                                                                        |
| Rated voltage                    | 12V DC                                                                                                                       |
| Operating voltage                | 7.0V - 13.2V DC                                                                                                              |
| Starting voltage                 | 7.0V DC                                                                                                                      |
| Rated current                    | 0.075A (+/-10%)                                                                                                              |
| Rated power consumption          | 0.90W (+/-10%)                                                                                                               |
| Locked rotor protection          | Auto power off after locked at rated voltage for 1 sec. After auto power off, the circuit attempts to restart in 2 to 6 sec. |
| Polarity protection              | Open circuit when Vcc & GND are exchanged. Circuit won't be burned within 5 sec when Vcc & GND are exchanged.                |

### 2.3. Insulation

|                       |                                                                     |
|-----------------------|---------------------------------------------------------------------|
| Insulation resistance | 10 MΩ / between unshielded wire and frame at 500 VDC/min            |
| Dielectric strength   | 5 mA max. / measured between lead wire (+) and frame at 500 VAC/min |



## 2.4. RPM signal specification



\*\* Please select "R" to make "Link"


Within 1~5 mA

If you need higher pull-up voltage, please contact Noctua.

\*\* 13.2V Max

5mA Max

### Output Waveform



## 2.5. PWM duty cycle operating points

PWM Control Input (W)



PWM frequency = 18 KHz to 30 KHz

High Level = 3.3V to 6V

Low Level = 0V to 0.4V


PWM Range = 20 % to 100 %



Fan stops at 0% PWM duty cycle.

The starting voltage must be the same as the rated voltage.

| Duty cycle (%) | RPM  | Tolerance |
|----------------|------|-----------|
| 0              | stop | 0         |
| 20             | 270  | +/- 30%   |
| 40             | 550  | +/- 10%   |
| 60             | 825  | +/- 10%   |
| 80             | 1070 | +/- 10%   |
| 100            | 1200 | +/- 10%   |




### 3. Performance specifications

#### 3.1. General performance specifications (+/- 10%)

|                  |             |
|------------------|-------------|
| Rotational speed | 1200 rpm    |
| Airflow          | 100.6 m³/h  |
| Acoustical noise | 18.1 dB(A)  |
| Static pressure  | 1.31 mm H2O |
| MTTF (at 40°C)   | > 150,000 h |

#### 3.2 Performance curve

|   | Airflow [m³/h] | Pressure [mm H2O] |
|---|----------------|-------------------|
| 1 | 100.60         | 0,0               |
| 2 | 76.50          | 0.34              |
| 3 | 50.30          | 0.49              |
| 4 | 24.90          | 0.98              |
| 5 | 0.00           | 1.31              |



## 4. Remarks

Noctua makes no warranties and disclaims all warranties, expressed or implied, or statutory related to these specifications. Noctua is not liable for any incompleteness or inaccuracies as well as consequential, incidental or indirect damages relating to the specifications or their use. The user assumes the full risk of using this specification. Under no circumstances shall Noctua be liable for any actual, direct, indirect, punitive, or consequential damages arising from such use, even if advised of the possibility of such damages.

Noctua doesn't take any responsibility if the product is used outside the specified parameters.

Specifications are obtained after 5 minutes of operation at 25 °C and 65% humidity. The fan was mounted vertically in free air conditions.

Please note that excessive humidity can be harmful to the product and it should therefore be stored in cool, dry environments only. If the product was stored at less than 5 °C for more than several hours, it should be stored at more than 20 °C for at least 24 hours before use.

Handle the fan with care. Applying pressure or force upon the impeller or dropping the fan can result in damage. Take the necessary precautions (fan grills, etc.) to prevent injuries. Do not touch the fan blades during operation.

Please ensure the correct polarity. As the fan doesn't have a protection against reverse polarity, reverse connection can lead to damage.

Please make sure that the fan is properly mounted. Noctua cannot be held responsible for vibrations or other noises caused by improper installation.

