



NOCTUA NF-F12 industrialPPC-24V-3000 IP67 PWM

120x120x25mm Fan

industrialPPC

Conceived for industrial heavy duty applications that require enhanced cooling performance and advanced ingress protection, the NF-F12 industrialPPC (Protected Performance Cooling) is a ruggedised high-speed version of the award-winning retail model. The 24V variant uses a dedicated wide input range version of Noctua's NE-FD2 motor driver IC in order to support 24V-based industrial applications. Thanks to the outstanding aerodynamic efficiency of the NF-F12 design and the use of a novel three-phase motor, the industrialPPC version provides superior airflow and pressure capacity while keeping noise levels and power consumption moderate as against comparable high-speed fans. While its fibre-glass reinforced polyamide construction and certified water and dust protection make the NF-F12 industrialPPC suitable for operation in challenging environments, the renowned SSO2 bearing technology guarantees an MTBF of over 150.000hrs. Topped off with Noctua's trusted reliability and 6 years manufacturer's warranty, the NF-F12 industrialPPC is an ideal choice for highly demanding applications that require superior flow rates and ultimate dependability.

24V version

The industrialPPC 24V models use a dedicated wide input range version of Noctua's NE-FD2 three-phase motor driver IC. Supporting operating voltages from 6 to 30V, these models are ideal for 24V-based industrial applications and voltage-based speed control.

Lower speed and noise levels in 12V PC environments

While the industrialPPC 24V model has been designed with 24V industrial applications in mind, it runs at a maximum speed of around 3000rpm in 12V PC environments and can be slowed down further via PWM, thus combining industrialPPC features and design with Noctua's signature quietness.

Size	120 x 120 x 25 mm
Bearing	SSO2
Blade Geometry	A-Series with Flow Acceleration Channels
Frame Technology	AAO (Advanced Acoustic Optimisation)
IP Rating / Connector	67 / 4-pin PWM
Input Power / Operating Voltage	4.32 W / 24 V
MTBF	> 150.000 h

Max. Rotational Speed 12V (+/-10%)	1600 RPM
Max. Rotational Speed 24V (+/-10%)	3000 RPM
Max. Airflow	186.7 m³/h
Max. Acoustical Noise	43.5 dB(A)
Max. Static Pressure	7.63 mmH2O

Product Name
Noctua NF-F12 industrialPCC-24V-3000 IP67 PWM

EAN-No.
4716123315711

UPC-No.
842431012586

Packaging Dimensions (HxWxD)
180 x 170 x 34 mm

Weight incl. Packaging
270 gr

Warranty
6 Years

MSPR
29.90 EUR

Packaging Unit
20 Pcs.

Packaging Dimensions / Unit (HxWxD)
380 x 360 x 200 mm

Weight incl. Packaging / Unit
6.3 kg

Scope of Delivery
Fan, 4 Fan Screws

